



Manual Multi-Port Valve

1. Adopt the high degree pottery, seal slice with scuff resistance, corrosion proof, perfect, sealing, and long time for using,
2. Reasonable fluid design: Service—Fast Rinse—Backwash—Fast-Rinse—Service.
3. Small rotation angle for closing and opening, It feel swell for operation.
4. It could operation with pressure, no leakage.

No	Product name	Model	Flow	Distributor pilot	Inlet/Outlet	Apply Tank
			(m ³ /h)			(mm)
1	Manual filter valve	F56E	2	3/4 inch	3/4 inch	Φ200×350
2	Manual soften valve	F64B	2	3/4 inch	3/4 inch	Φ200×350
3	Manual filter valve	F56A	4.5	3/4 inch	1 inch	Φ200×400
4	Manual soften valve	F64A1	4.5	3/4 inch	1 inch	Φ250×400
5	Manual soften valve	F64A2	4.5	3/4 inch	1 inch	Φ250×400
6	Manual filter valve	F56D-1	8	1.5 inch	2 inch	Φ500×900
7	Side manual filter valve	F56D-2	8	1.5 inch	2 inch	Φ500×900
8	Manual soften valve	F64D-1	8	1.5 inch	2 inch	Φ500×900
9	Side manual soften valve	F64D-2	8	1.5 inch	2 inch	Φ500×900
10	Manual filter valve	RY-F56E	2	1/2 inch	1/2 inch	Φ200×350
11	Manual filter valve	RY-F56A	2	3/4 inch	1 inch	Φ200×400
12	Manual filter valve	RY-F56A	4.5	1 inch	1 inch	Φ200×400
13	Manual filter valve	RY-JD	4.5	3/4 inch	1 inch	Φ250×400

Dongguan Wellsource Water Treatment Co.Ltd



Automatic Multi-Port Valve

1. More reliable way of opening and close
2. Keyboard locked function: The key set will lock automatic exceed one minute, you must open the lock over again when you operate, prevent wrong operation.
3. It adopts LED dynamic colorful screen: The colorful screen flicker express it is in the state of running, otherwise express it is in the state of regeneration.
4. Prompt power cut secularly: Out of electricity exceed three days, you must reinstall the currently time when the timepiece flicker ceaselessly, the already setting time is not changed.
5. Two kinds of counted modes for running: switch the ON and 1 which in the electrical control main board to reach the purpose of running by day or hour.
6. Having output signal connector: via three port of open, close, common down-lead to connect the electromagnetism valve or increase-pressure pumps.
7. Washing several times Progress could set up several washing times, which means it running one time then backwash, fast rinse several times (could be set).
8. No coming water while single pot type control valve regeneration

No	Product name	Model	Flow	Distributor pilot	Inlet/Outlet	Apply Tank
			(m ³ /h)			(mm)
1	Automatic filter valve	F71B	2	3/4 inch	3/4 inch	Φ200×350
2	Automatic soften valve	F65B	2	3/4 inch	3/4 inch	Φ200×350
3	Automatic filter valve	F67B	4.5	3/4 inch	1 inch	Φ250×400
4	Automatic soften valve	F63B	4.5	3/4 inch	1 inch	Φ250×400
5	Automatic filter valve	F75A	10	1.5 inch	2 inch	Φ500×900
6	Automatic soften valve	F74A	10	1.5 inch	2 inch	Φ500×900
7	Automatic filter valve	F77A	18		2 inch	Φ1000×1200

Dongguan Wellsource Water Treatment Co.Ltd

8	Automatic soften valve	F77B	18		2 inch	Φ1000×1200
9	Automatic filter valve	F78B	40			Φ1200×1500
10	Automatic soften valve	F78A3	40			Φ1200×1500

Tel:86-769-88412810 88412820

Fax:86-769-28687086

Email:leo@waterwellsource.com

Web:waterwellsource.com