

Dongguan Wellsource Water Treatment Co.Ltd



Bag Filter (SUS304)

No	Product Name	Model	Filter flow rate	Inlet/Outlet nozzle
1	Bag Filter (Clamp-on)	φ230x410x1Bag	10-20	DN40
2	Bag Filter (Clamp-on)	φ230x810x1Bag	30-45	DN50
3	Bag Filter (Flange)	φ230x410x1Bag	10-20	DN50
4	Bag Filter (Flange)	φ230x810x1Bag	30-45	DN50
5	Bag Filter (Flange)	φ450x410x2Bag	20-40	DN65
6	Bag Filter (Flange)	φ450x810x2Bag	30.0-60	DN65
7	Bag Filter (Flange)	φ500x410x3Bag	40-50	DN80 Flange
8	Bag Filter (Flange)	φ500x810x3Bag	80-100	DN80 Flange
9	Bag Filter (Flange)	φ550x410x4Bag	50-70	DN80 Flange
10	Bag Filter (Flange)	φ550x810x4Bag	110-130	DN80 Flange
11	Bag Filter (Flange)	φ600x410x5Bag	60-80	DN100 Flange
12	Bag Filter (Flange)	φ600x810x5Bag	140-160	DN100 Flange
13	Bag Filter (Flange)	φ700x810x6Bag	160-200	DN125 Flange
14	Bag Filter (Flange)	φ800x810x8Bag	200-350	DN150 Flange

Dongguan Wellsource Water Treatment Co.Ltd



UPVC Bag and Cartridge Filter Housing

Material: UPVC
Work Pressure:0.4MPA

No	Product Name	Model	Filter flow rate	Inlet/Outlet nozzle
1	Bag Filter	HXP-BF-1-1	φ225X780	DN50
2	Bag Filter	HXP-BF-1-2	φ225X1180	DN50
3	Exactitude Filter (10inch 5channel)	HPCF-5DC1	φ225x450	DN40
4	Exactitude Filter (20inch 5channel)	HPCF-5DC2	φ225X700	DN40
5	Exactitude Filter (30inch 5channel)	HPCF-5DC3	φ225X950	DN40
6	Exactitude Filter (40inch 5channel)	HPCF-5DC4	φ225X1200	DN40

Bag Filters are the workhorse of the filtration industry.

In general, Felt Type Filter Bags are finer and offer higher solids loading capacity at 150 microns and below.

Above 150 Microns Mesh Type Filter Bags dominate in their more traditional straining applications. Most Bag filters are also designed disposable, which means that they have to be replaced when the filter is clogged.

Features:

1. Well sealed, no side leaking
2. Large effective filtration area
3. High filtration efficiency
4. Filter bag can be replaced easily
5. Small product size, large filtration capacity
6. Steady quality, long using life